

511,066

RECEIVED 12 OCT 2004 2004

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
23 October 2003 (23.10.2003)

PCT

(10) International Publication Number  
**WO 03/087646 A1**

(51) International Patent Classification<sup>7</sup>: **F16L 17/10, 37/00**

Jean, Maureen of P.O. Box 100, 87 Woodland Road, Darlington, County Durham, DL3 7UE (GB).

(21) International Application Number: PCT/GB03/01509

(72) Inventor: **BALL, Daniel, Graham** (deceased).

(22) International Filing Date: 8 April 2003 (08.04.2003)

(74) Agent: **MARSHALL, John, Grahame**; Serjeants, 25 The Crescent, King Street, Leicester LE1 6RX (GB).

(25) Filing Language: English

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(26) Publication Language: English

(30) Priority Data:  
0208098.4 9 April 2002 (09.04.2002) GB


(71) Applicant (*for all designated States except US*): **GLOWAY INTERNATIONAL INC.** [—/—]; Trident Chambers, P.O. Box 146, Road Town, Tortola (VG).

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

(71) Applicant (*for US only*): **BALL, Jean, Maureen** (legal representative of the deceased inventor) [GB/GB]; Ball,

[Continued on next page]

(54) Title: PIPE REPAIR SYSTEM AND DEVICE



(57) Abstract: The invention provides a coupling member for use in the repair of pipes and pipelines of from 90mm to 250mm in diameter, such as those used for the pipeline transportation and delivery of domestic and industrial liquids such as water, gas, oil and other petrochemicals. Two coupling members are used for each repair. Each has a first collar portion for surrounding the new pipe section and a second collar portion for surrounding a cut end portion of the old pipe section, and the two pipe connectors are located with their respective first collar portions adjacent to one another and their respective second collar portions facing mutually outwardly towards the opposite ends of the new pipe section. Pressure chambers are formed between the annular grooves and the seal members of the first collar portions and between the annular grooves and the nitrile rubber sealing rings of the second collar portions.



WO 03/087646 A1